

SC COLOR™ PRODUCT DATA SHEET



DESCRIPTION

SC Color™ are conveniently premeasured to individually tint any single overlay bag mix. SC Color color packs are pure, synthetic, iron oxide pigments that are UV stable and contain no fillers that will affect the performance of the overlay bag mix being tinted. Color consistency is maintained from sack to sack.

MIXING & APPLICATION

1. Add required water to a 5 gal. (18.9 liter) pail as directed by appropriate overlay bag mix TDS.
2. Empty SC Color into water prior to addition of dry bag mix.
3. Mix with a handheld concrete mixer with a cage mixer blade, such as an Eibenstock model #EHR 20R 4. While mixing add overlay bag mix as directed in appropriate TDS. Note: multiple bag batches may be appropriate; always maintain mix ratio of 1 – SC Color (color pack) to 1 – overlay bag mix for color consistency.



SUITABILITY SAMPLE

Because job site conditions and requirements can vary significantly, always prepare a sample. This is especially critical for custom coloration.

DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

LIMITATIONS

For use by trained professionals that have read the complete SDS. The aggregate of vertical overlay bag mixes may affect final color to vary from color chart. Always prepare a sample.

QUICK FACTS

PACKAGING

0.5 lb. (0.23 kg) Sack

COVERAGE

1-SC Color (color pack) to 1-50 lb. (22.7 kg) overlay bay mix (white)

COLOR

30 Standard Colors
Custom Colors Available

SHELF LIFE

Under normal conditions: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened sack is (12) months from the date of purchase. Storage must be under roof and off the floor. Rotate inventory to maintain product that is within limits.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/ seller's option. SureCrete LLC shall not be liable for cost of labor or direct and/or incidental consequential damages.

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. When used according to direction, no hazard is anticipated. Inhalation: Avoid prolonged breathing of airborne dust, particularly present during mixing. Use NIOSH approved respirator for nuisance if threshold limit values are unsafe. Skin Contact: Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. Eyes: Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

SAFETY DATA SHEETS

The following are links to all available safety data sheets related to this product:

[SC Color Safety Data Sheet \(SDS\)](#)

MANUFACTURER PART #'S

Almond	SKU# 35103004-01
Antique White	SKU# 35103004-02
Brown Derby	SKU# 35103004-04
Blue Fog	SKU# 35103004-03
Caribbean Cream	SKU# 35103004-05
Concrete Gray	SKU# 35103004-08
Charcoal	SKU# 35103004-06
Chocolate	SKU# 35103004-07
Coral	SKU# 35103004-09
Dove Gray	SKU# 35103004-12
Desert Sand	SKU# 35103004-11
Dark Walnut	SKU# 35103004-10
Gray	SKU# 35103004-13
Green Slate	SKU# 35103004-14
Ivory	SKU# 35103004-15
Limestone	SKU# 35103004-16
Mint	SKU# 35103004-18
Maplewood	SKU# 35103004-17
Natural White	SKU# 35103004-19
Old Brick	SKU# 35103004-20
Putty	SKU# 35103004-21
Redwood	SKU# 35103004-22
Sand Buff	SKU# 35103004-23
Smoke	SKU# 35103004-25
Spice	SKU# 35103004-26
Silver	SKU# 35103004-24
Sun Buff	SKU# 35103004-27
Terra Cotta	SKU# 35103004-29
Taupe	SKU# 35103004-28
Tile Red	SKU# 35103004-30
Custom Color	SKU# 35103004-00

VOC REGULATORY COMPLIANCE

AIM	OTC	LADCO	CARB	SCAQMD	CANADA
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>