



SURECRETE®



View More Info for this Product at
www.surecretedesign.com/tds/surface-prep-faststrip-plus-tds.pdf

FAST STRIP PLUS

HEAVY DUTY SOLVENT BASED
SEALER & COATING REMOVER

DESCRIPTION

Fast Strip Plus is a high-powered, solvent-based stripper for heavy coatings and the most difficult to remove sealers. Specially formulated to be used when mechanical removal is not desired. Fast Strip Plus™ can be used outside, wherever water can be used to flush off the dissolved sealer, and good ventilation is available. Fast Strip Plus contains biodegradable surfactants and non-chlorinated solvents.

BENEFITS

- Strong Chemical Stripper
- Works faster than Citrus-Based Strippers
- No Neutralizing Necessary
- Dissolves Heavy Grease and Soil Deposits

APPLICATION

NOTE:

Test in a small area before applying Fast Strip Plus across the complete area.

Fast Strip Plus™ may be sprayed from a solvent resistant sprayer, brushed, or poured on and squeegeed evenly across the surface to be treated. Apply at the rate of approximately 1 gallon per 150 ft² (13.9 m² per 3.8 L). Allow Fast Strip Plus to stand for a minimum of 20 – 30 minutes to soften sealer, coating, grease, or soil.

Add a small amount of water and scrub vigorously to emulsify the coating. Heavy coatings may require additional treatment. Scrape up residue and store for disposal, rinse thoroughly with water. Flush away dissolved residue or vacuum up and rinse clean. Exercise caution for creating a source of ignition with electrical tools, fuel burning appliances, and other sources, as Fast Strip Plus is flammable. Use protective gear including respirator and provide proper ventilation.

SUITABILITY SAMPLE

Always prepare an adequate number of on-site test areas on the intended substrate to establish aesthetic suitability for products' intended use.

CLEANUP

Before Fast Strip Plus™ dries; spills and tools can be cleaned up with water.

DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

LIMITATIONS

- For use by trained professionals that have read the complete SDS.
- Fast Strip Plus™ is extremely flammable, do NOT use near any ignition sources.
- Do Not dilute Fast Strip Plus™.
- Not for the removal of cementitious coatings
- Not recommended for wood surfaces.
- Do Not allow excess buildup to occur.

QUICK FACTS

PRODUCT NAME Fast Strip Plus™

PACKAGING

5-gallon pail (18.9 L)

COVERAGE

Varies upon substrate porosity, texture, and application method: 150 ft² per gal (14 m² per 3.8 L)

SHELF LIFE

Under normal conditions Fast Strip Plus™: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened container is 1 year from the date of purchase. Storage must be under roof, off the floor, and protected from freezing. Rotate inventory to maintain product that is within limits.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/seller's option. SureCrete Design Products shall not be liable for cost of labor or direct and/or incidental consequential damages. consequential damages.

WARNING

KEEP OUT OF REACH OF CHILDREN. Inhalation: Avoid prolonged breathing of airborne dust, particularly present during mixing. Use NIOSH approved respirator for nuisance if threshold limit values are unsafe. Skin Contact: Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. Eyes: Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

PROPERTIES

Appearance	Yellow/straw color
Storage Stability	1 year
Odor	Solvent
Application Temperature	40°F – 85°F (4°C - 29°C)

SAFETY DATA SHEETS (SDS)

The following are links to all available safety data sheets related to this product:

[Fast Strip Plus Safety Data Sheet \(SDS\)](#)

MANUFACTURER PART

5-gallon pail (18.9 L)

SKU # 15102011