



SAFETY DATA SHEET

SECTION 1 Product and Company Identification

Product

Product Name: Trans4loor Metallic Epoxy Base Coat, Clear, Part B

Product Description: 100% Solids Epoxy Base Coat / Part B

Product Code: SC-T4-01-1B

Intended Use: High build 100% solids, solvent free polyamine epoxy system for decorative epoxy applications.

/ Resin

Company

Manufacturer: SureCrete Design Products, Inc.

15246 Citrus Country Drive

Dade City, FL 33523

USA

Contact: 1-352-567-7973 (telephone general)

1-800-262-8200 Chemtrec

+1 703-741-5500 Chemtrec International info@surecretedesign.com (e-mail)

1-352-521-0973 (facsimile)

SECTION 2: HAZARDS IDENTIFICATION SIGNAL WORD: DANGER









HAZARD CLASS FLAMMABLE LIQUIDS ACUTE TOXICITY ACUTE TOXICITY **ACUTE TOXICITY**

SKIN CORROSION/IRRITATION SERIOUS EYE DAMAGE/IRRITATION RESPIRATORY SENSITIZER

TOXIC TO SPECIFIC TARGET ORGAN TOXICITY

SINGLE EXPOSURE ASPIRATION HAZARD

HAZARDOUS TO THE AQUATIC ENVIRONMENT HAZARDOUS TO THE AQUATIC ENVIRONMENT

CHRONIC 2

HAZARD STATEMENTS:

H227

H302+H312+H332 H304

H315 H318 COMBUSTIBLE LIQUID

HAZARD CATEGORY

CATEGORY 4 ORAL

CATEGORY 4 DERMAI

CATEGORY 4 INHALATION

CATEGORY 3

CATEGORY 2

CATEGORY 1

CATEGORY 1 **CATEGORY 3**

CATEGORY 1

ACUTE 2

HARFMUL IF SWALLOWED, IN CONTACT WITH SKIN OR IF INHALED

MAY BE FATAL IF SWALLOWED OR ENTERS AIRWAY

CAUSES SKIN IRRITATION CAISES SERIOUS EYE DAMAGE





H334 MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES

IF INHALED

H335 MAY CAUSE RESPIRATORY IRRITATION

TOXIC TO AQUATIC LIFE WITH LONG-LASTING EFFECTS H411

PRECAUTIONARY STATEMENTS:

PREVENTION

P271

P312 P321

P322 P330

P331

P332 P332+P313

P342+P311 P362

P370+P378

P210 KEEP AWAY FROM HEAT/HOT SURFACES/SPARKS/OPEN FLAMES AND OTHER

SOURCES OF IGNITION. NO SMOKING. P233 KEEP CONTAINER TIGHTLY CLOSED

GROUND AND BOND CONTAINER AND RECEIVING EQUIPMENT P240

USE EXPLOSION PROOF ELECTRICAL/VENTILATION/LIGHTING/HANDLING P241

FOUIPMENT

USE NON-SPARKING TOOLS P242

TAKE ACTION TO PREVENT STATIC DISCHARGE P243

P261 AVOID BREATHING DUST/FUME/GAS/MIST/VAPOR/SPRAY

WASH HANDS AND ANY EXPOSED AREA THOROUGHLY AFTER HANDLING P264 P270

DO NOT EAT, DRINK, OR SMOKE WHILE USING THIS PRODUCT USE ONLY OUTDOORS OR IN WELL-VENTILATED AREA

AVOID RELEASE TO THE ENVIRONMENT P273

P280 USE APPROPRIATE PERSONAL PROTECTIVE IMPERVIOUS GLOVES/PROTECTIVE

WEAR PROTECTIVE IMPERVIOUS GLOVES/OSHA APPROVED EYE PROTECTION/

FACE PROTECTION

IN CASE OF INADEQUATE VENTILATION, WEAR APPROPRIATE ORGANIC VAPOR P285

RESPIRATORY PROTECTION

RESPONSE: P301+P310 IF SWALLOWED, IMMEDIATELY CALL A POISON CENTER/DOCTOR

IF ON SKIN (OR HAIR) TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. P303+P361+P353

RINSE SKIN WITH WATER (OR SHOWER)

P304+P340 IF INHALED; REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR

BREATHING.

P305+P351+338 IF IN EYES, RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE

CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL

SPECIFIC TREATMENT (SEE ON THIS LABEL)

SPECIFIC MEASURES (SEE ON THIS LABEL)

RINSE MOUTH

DO NOT INDUCE VOMITING

IF SKIN IRRITATION OCCURS;

IF SKIN IRRITATION OCCURS; GET MEDICAL ATTENTION/ADVICE

IF EXPERIENCING RESPIRATORY SYMPTOMS, CALL A POISON CENTER/DOCTOR

TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

IN CASE OF FIRE, USE CARBON DIOXIDE (CO2), POWDER, ALCOHOL-RESISTANT

FOAM TO EXTINGUISH

STORAGE:

P403+P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P403+P235

STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

STORE LOCKED UP.

DISPOSAL:

P405

STORE SEPARATELY. DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH P501

ALL LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS.



SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Hazard Ratings

	health	flammability	reactivity	PPE
HMIS	2	1	0	В

SECTION 3 Composition / Information on Ingredients

This material is regulated as a mixture

COMPONENT	CAS#	PERCENT	EXPOSURE LIMITS OSHA PEL ACGIH TLV OTHER
Benzyl Alcohol	100-51-6	35-45	NOT ESTABLISHED
4-Nonyl Hydroxybenzene, Nonylphenol	84852-15-3	20-25	NOT ESTABLISHED
Isophorone Diamine	2855-13-2	15-20	NOT ESTABLISHED
Cumene	98-82-8		50 ppm

⁺ Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 4 First Aid Measures
PRIMARY ROUTES OF EXPOSURE:

Skin contact.

DESCRIPTION OF FIRST AID MEASURES:

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomitting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns.

SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

CHRONIC HEALTH EFFECTS:

No anticipated chronic effects.

[^] Hazardous Air Pollutant established by the EPA as directed by the Clean Air Act of 1990



MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Treat symptomatically.

SECTION 5 FIRE AND EXPLOSION HAZARD DATA

SUITABLE EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIFIC HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

In the event of fire, harmful vapors including carbon monoxide, carbon dioxide, and others may be released. There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment listed in section 8.

ENVIRONMENTAL PRECAUTIONS:

Keep runoff from storm sewers ditches, streams, lakes and other ground waters and waterways.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:

Contain all spills. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Collect into suitable containers and dispose of properly in accordance with all applicable regulations. (See Section 13) Rinse affected area thoroughly with water.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

PRECAUTIONS FOR SAFE STORAGE:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical



damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS: SEE SECTION 3 FOR OCCUPATIONAL EXPOSURE LIMIT VALUES

ENGINEERING CONTROLS: General room ventilation is adequate.

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE: Liquid ODOR: Amine or ammonia odor ODOR THRESHOLD: Not measured MELTING/FREEZING POINT: Not Determined SPECIFIC GRAVITY (H20=1): 1.03 EVAPORATION RATE: Not Determined FLASH POINT: Greater than 200 FPMCC **UPPER EXPLOSION LIMIT: 6.6** LOWER EXPLOSION LIMIT: 1

DECOPMPOSITION TEMPERATURE: Not Available COATING V.O.C.: 9 g/l (0.08 lb/gl)

COLOR: Various colors pH: Not Determined SOLUBILITY IN WATER: Dilutable

BOILING POINT/RANGE:

VAPOR DENSITY: Greater Than Air FLAMMABILITY: Not determined

VAPOR PRESSURE: Not Determined

AUTO-IGNITION TEMPERATURE: Not Determined PARTITION COEFFI-

CIENT: Not Available VISCOSITY: Not Determined

SECTION 10 STABILITY AND REACTIVITY DATA

REACTIVITY: Will not occur.



CHEMICAL STABILITY:

Stable under normal conditions and handling.

POSSIBILITY OF HAZARDOUS REACTIONS:

No hazardous reactions if stored and handled as prescribed/indicated.

CONDITIONS TO AVOID:

None known

INCOMPATIBLE MATERIALS:

Avoid exposure to strong oxidizing agents and reducing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

SECTION 11 TOXICOLOGICAL INFORMATION

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY:

No data available.

PERSISTENCE AND DEGRADABILITY:

Not readily degradable.

BIOACCUMULATIVE POTENTIAL:

No data available.

MOBILITY IN SOIL:

No data available.



OTHER ADVERSE EFFECTS: No known effects or critical hazards. No data available. Nonylphenol is a marine pollutant.

SECTION 13 DISPOSAL CONSIDERATIONS

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261,however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SECTION 14 TRANSPORT INFORMATION

PROPER SHIPPING NAME: (UN #, SHIPPING NAME, HAZARD CLASS, PACKING GROUP) UN3066, Paint, 8, III

SECTION 15 REGULATORY INFORMATION

US TOXIC SUBSTANCE CONTROL ACT (TSCA):

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

SARA 311/312 HAZARDOUS CHEMICAL: SEE SECTION 3

SARA 313 (TRI REPORTING):

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 3.

STATE LISTED COMPONENTS CAS NUMBER STATE CODE

Cumene 98-82-8 CA,CT,FL,IL,LA,MA,ME,MN,NJ,PA,RI

CALIFORNIA PROPOSITION 65

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

Cumene CAS#98-82-8 CANCER

SECTION 16 OTHER INFORMATION

REVISION DATE: 01/04/21

To the best of our knowledge the information contained here is accurate. However, neither the above named manufacturer nor any of its distributors assumes any liability whatsoever for the accuracy or the completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described



herein, we cannot guarantee that these are the only hazards that exist.