

www.SureCreteDesign.com



Tools and Supplies

SURERELEASE LIQUID

LIQUID STAMPING RELEASE AGENT



View More Info for this Product at http://www.surecretedesign.com/surerelease/



SURERELEASE STAMPING LIQUID RELEASE

DESCRIPTION

SureCrete *SureRelease Liquid* is a colorless, bubblegum scented petroleum distillate formulated to release any decorative imprinting tool from concrete or polymer modified cementitious topping. *SureRelease* provides a lubricating barrier that protects and prolongs the life of stamping tools and evaporates from the cementitious surface leaving minimal residue.

USE

Specifically designed for use in conjunction with SureCrete Systems: stamped concrete, stamped overlay, texture systems and imprinting, stamp tools. May be used on interior or exterior. SureCrete recommends *SureRelease* for projects that are to be textured, but colored later, e.g. stamp overlay and stamp concrete. Excessive masking associated with messy powder release is virtually elimi-nated with *SureRelease*.

APPLICATION

Application of *SureRelease* is accomplished through misting the cementitious surface with a pump-up sprayer. Imprinting tools must have their tex-ture face saturated at the start of stamping. Apply only as much release as can be covered with tools in a few minutes in temperatures above 40°F and rising. Direct sunlight and windy conditions will accelerate the evaporative properties of *SureRelease*.

CLEAN-UP

Before *SureRelease* dries; spills and tools can be cleaned up with a solvent such as xylene or acetone.

DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

LIMITATIONS

For use by trained professionals that have read the complete SDS.



PACKAGING

5 gal (18.9 L) pails

COVERAGE

Approx. 240 ft² per gallon (5.9 m²/L)

PHYSICAL PROPERTIES

Appearance: clear VOC: 0 g/L Odor: bubblegum

SHELF LIFE

Under normal conditions: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened container is (12) months from the date of purchase. Storage must be under roof and off the floor. Avoid temperature extremes. Rotate inventory to maintain product that is within limite

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/seller's option. Sure-Crete Design Products shall not be liable for cost of labor or direct and/or incidental consequential damages.

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. Inhalation: Avoid prolonged breathing of product. Use NIOSH approved respirator if threshold limit values are unsafe. Skin Contact: Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. Eyes: Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

SAFETY DATA SHEETS

The following are links to all available safety data sheets related to this product:

 http://www.surecretedesign.com/sds/tools-supplies-liquidrelease-sds.pdf

